



Barra a filettatura continua Hollow continuously threaded bar Stange gerolt auf ganzer lange	Code	L20	L25	L28	L32	L40	L63,5
Ø A / Ø max B	mm	20/23	25/29	28/32	32/36	40/45	63,5/70
Tensione di rottura Tensile strenght Bruchlast	N/mm ²	550					
Tensione di snervamento Yeld point Elastizitgrenze	N/mm ²	500					
Allungamento Elongation Bruchdehnung	%	min 10 %					
Carico al limite elastico Yeld point Steckgrenze	kN	160	245	310	405	630	1760
Carico di rottura Tensile strenght Bruchlast	kN	175	270	340	440	690	2215
Sezione media Sectional area Querschnitt	mm ²	314	491	616	804	1260	3167
Peso per metro lineare Weight Gewicht	kg/mt	2,47	3,85	4,83	6,31	9,87	24,85

Accessori - Accessories - Zubehor

Manicotto di giunzione Coupling Muffe	Code	ML20	ML25	ML28	ML32	ML40	ML63,5
	mm	36 x 105	40 x 115	45 x 125	52 x 140	65 x 180	90 x 200

Dado di bloccaggio Nut Mutter	Code	DL20	DL25	DL28	DL32	DL40	DL63,5
	mm	36 x 40	41 x 45	46 x 50	50 x 60	65 x 80	90 x 90

Piastra in acciaio Plate Platte	Code	PR150x8	PRB150x8	PR150x10	PR200x10	PRB200x10	PR200x12
	mm	150x150x8	150x150x8 bombata	150x150x10	200x200x10	200x200x10 bombata	200x200x12